#### INPUT: RGB IN1=projector & computer RGB IN2=projector & Elmo

# To use the ELMO:

- 1. Plug in the cart.
- 2. Turn **ELMO** power switch ON.
- 3. Turn **PROJECTOR** power switch ON.
- 4. When power light is steady orange: Press <u>Standby/On</u> button.
- 5. Wait until power light is steady green, then: Press <u>Input button</u> until screen shows RGB IN2.

### To turn off:

- 1. Turn ELMO power switch to OFF.
- 2. Press PROJECTOR Standby/on button once.
- 3. Press <u>Standby/on</u> button again. (Press as soon as the *Power Off?* Message appears on the screen.)
- 4. The power light will be blinking orange.

\*\*\*WAIT until the power light is steady orange (The fan should now be off.)

- 5. Then you may turn **PROJECTOR** power switch OFF.
- 6. Unplug the cart.

## To use the computer & projector:

- 1. Plug in the cart.
- 2. If using the network, plug the <u>network cable</u> into your wall network outlet.
- 3. Turn on the computer .
- Turn on the computer monitor. 4. Turn **PROJECTOR** power switch ON.
- 5. When power light is steady orange:
- Press <u>Standby/On</u> button.
- 6. Wait until power light is steady green, then: Press <u>Input button</u> until screen shows RGB IN1. (The screen should now show whatever is on your computer screen.)

### To turn off:

- 1. Press **PROJECTOR** <u>standby/on</u> button once.
- 2. Press <u>Standby/on</u> button again.

(Press as soon as the *Power Off?* Message appears on the screen.)

3. The power light will be blinking orange.

\*\*\*WAIT until the power light is steady orange. (The fan should now be off.)

- 4. Then you may turn **PROJECTOR** power switch OFF.
- 5. Shutdown the computer.
- 6. Turn off the monitor
- 7. Unplug the cart.